



Washer Head Construction Lag Screw

5/16 x 2^{1/2}" to 3/8 x 12" lengths

Type 17 Notched Extra Sharp Point

- Starts quickly without 'walking'
- Significantly reduces splitting & drive torque requirements by removing wood from the hole as the screw penetrates instead of forcing the wood apart

Significantly Reduces Need for Pre-Drilling!

Deep, Wide, Sharp Threads w/ Spiral Notches

- Reduces driving torque needed

Hardened Heat-Treated Steel

- Exterior ceramic coating on 2^{1/2}" to 6" sizes
- Yellow zinc coating on 7" to 12" sizes

Smooth Edges

- Give a finished appearance

Built-On Round Washer Head

- 5/8" diameter on 2^{1/2}" to 6" sizes
- 11/16" diameter on 7" to 12" sizes

Star Drive Recess

- Reduces camout and end load
- Twice the torque of Phillips or square drive
- Eliminates spinning and fastener damage
- Two recess sizes (30 & 40) to match the torque requirements of the screw size
- Gives better bit life



Taylor Trading Co.

www.TaylorTradingCo.com

7638 Nashville Street Ringgold,
Georgia 30736 706-965-4587
phone 706-965-4597 fax

Available Lag Screw Packaging:



By the Each

100 ct. Clear

Plastic Jars

with screw-on lids



Bulk Cartons

Quantity	1-99	100	250
5" x 5/16"	.59	44.99	124.99
7" x 3/8"	.99	79.99	164.99
12" x 3/8"	1.99	174.99	334.99